Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 235328

FAIRCHILD SEMICONDUCTOR TM

www.fairchildsemi.com

UC3525A

SMPS Controller

Features

- 5V ± 1% Reference
- Oscillator Sync terminal
- Internal Soft Start
- Deadtime Control
- Under-Voltage Lockout

Description

UC3525A is a monolithic integrated circuit that Included all of the control circuit necessary for a pulse width modulating regulator. There are a voltage reference, an error amplifier, a pulse width modulator, an oscillator, under-voltage lockout, soft start circuit, and output drivers in the chip.

16-DIP

Internal Block Diagram



Rev. 5.0

©2000 Fairchild Semiconductor International

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Supply Voltage	V_{CC}	40	V
Collector Supply Voltage	V_C	40	V
Output Current, Sink or Source	I_O	500	mA
Reference Output Current	I_{REF}	50	mA
Oscillator Charging Current	$I_{CHG(OSC)}$	5	mA
Power Dissipation (T_A = 25°C)	P_D	1000	m/W
Operating Temperature	T_{OPR}	0 ~ +70	°C
Storage Temperature	T_{STG}	-65 ~ +150	°C
Lead Temperature (Soldering, 10 sec)	T_{LEAD}	+300	°C

Electrical Characteristics

(V_{CC} = 20V, T_A = -30°C to + 85°C, unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
REFERENCE SECTION						
Reference Output Voltage	V_{REF}	T_J = 25°C	5.0	5.1	5.2	V
Line Regulation	ΔV_{REF}	V_{CC} = 8 to 35V	-	9	20	mV
Load Regulation	ΔV_{REF}	I_{REF} = 0 to 20mA	-	20	50	mV
Short Circuit Output Current	I_{SC}	V_{REF} = 0, T_J = 25°C	-	80	100	mA
Total Output Variation (Note 1)	ΔV_{REF}	Line, Load and Temperature	4.95	-	5.25	V
Temperature Stability (Note 1)	ST_T	-	-	20	50	mV
Long Term Stability (Note 1)	ST	T_J = 125°C ,1 KHR_S	-	20	50	mV
OSCILLATOR SECTION						
Initial Accuracy (Note 1, 2)	ACCUR	T_J = 25°C	-	± 3	± 6	%
Frequency Change With Voltage	$\Delta f/\Delta V_{CC}$	V_{CC} = 8 to 35V (Note 1, 2)	-	± 0.8	± 2	%
Maximum Frequency	$f_{(MAX)}$	R_T = 2KΩ, C_T = 470pF	400	430	-	KHz
Minimum Frequency	$f_{(MIN)}$	R_T = 200KΩ, C_T = 0.1uF	-	60	120	Hz
Clock Amplitude (Note 1, 2)	$V_{(CLK)}$	-	3	4	-	V
Clock Width (Note 1, 2)	$t_{W(CLK)}$	T_J = 25°C	0.3	0.6	1	µs
Sync Threshold	$V_{TH(SYNC)}$	-	1.2	2	2.8	V
Sync Input Current	$I_{I(SYNC)}$	Sync = 3.5V	-	1.3	2.5	mA

Electrical Characteristics

(V_{CC} = 20V, T_A = 0 to +85°C, unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
ERROR AMPLIFIER SECTION (V_{CM} = 5.1V)						
Input Offset Voltage	V_{IO}	-	-	1.5	10	mV
Input Bias Current	I_{BIAS}	-	-	1	10	µA
Input Offset Current	I_{IO}	-	-	0.1	1	µA
Open Loop Voltage Gain	G_{VO}	R_L ≥10MΩ	60	80	-	dB
Common Mode Rejection Ratio	CMRR	V_{CM} = 1.5 to 5.2V	60	90	-	dB
Power Supply Rejection Ratio	PSRR	V_{CC} = 8 to 3.5V	50	60	-	dB
PWM COMPARATOR SECTION						
Minimum Duty Cycle	$D_{(MIN)}$	-	-	-	0	%
Maximum Duty Cycle	$D_{(MAX)}$	-	45	49	-	%
Input Threshold Voltage (Note 2)	V_{TH1}	Zero Duty Cycle	0.7	0.9	-	V
Input Threshold Voltage (Note 2)	V_{TH2}	Max Duty Cycle	-	3.2	3.6	V
SOFT-START SECTION						
Soft Start Current	I_{SOFT}	V_{SD} = 0V, V_{SS} = 0V	25	51	80	µA
Soft Start Low Level Voltage	V_{SL}	V_{SD} = 25V	-	0.3	0.7	V
Shutdown Threshold Voltage	$V_{TH(SD)}$	-	0.6	0.8	1	V
Shutdown Input Current	$I_{N(SD)}$	V_{SD} = 2.5V	-	0.3	1	mA
OUTPUT SECTION						
Low Output Voltage I	$V_{OL\ I}$	I_{SINK} = 20mA	-	0.1	0.4	V
Low Output Voltage II	$V_{OL\ II}$	I_{SINK} = 100mA	-	0.05	2	V
High Output Voltage I	$V_{CH\ I}$	I_{SOURCE} = 20mA	18	19	-	V
High Output Voltage II	$V_{CH\ II}$	I_{SOURCE} = 100mA	17	18	-	V
Under Voltage Lockout	V_{UV}	V_8 and V_9 = High	6	7	8	V
Collector Leakage Current	I_{LKG}	V_{CC} = 35V	-	80	200	µA
Rise Time (Note 1)	t_R	C_L = 1uF, T_J = 25°C	-	80	600	ns
Fall Time (Note 1)	t_F	C_L = 1uF, T_J = 25°C	-	70	300	ns
STANDBY CURRENT						
Supply Current	I_{CC}	V_{CC} = 35V	-	12	20	mA

Notes :

1. These parameters. although guaranteed over the recommended operating conditions, are not 100% tested in production
2. Tested at f_{OSC}=40 KHz (R_T =3.6K, C_T =0.01uF, R_I = 0Ω)

Test Circuit



Mechanical Dimensions

Package

16-DIP



Ordering Information

Product Number	Package	Operating Temperature
UC3525AN	16-DIP	-30 ~ +85°C

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR INTERNATIONAL. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

7/12/00 0.0m 001
Stock#DSxxxxxxxx
© 2000 Fairchild Semiconductor International